

DOCK-150 Series USB Chargers

INSTALLATION INSTRUCTIONS

For DOCK-150 Wireless Charger

Input rating: DC 5V, 6A

Output rating: Wireless charger: 5 watts Max.

USB charger: 1 x 2.4A (12 watts) Max.

2 x 1A (5 watts) Max.

CAUTION: To prevent the risk of fire and electric shock, please be sure to read all instructions before installing or using this unit.

IMPORTANT SAFETY INSTRUCTIONS

WARNING – To reduce the risk of fire, electric shock, or injury to persons:

1. Do not use power supply and cord(s) from 3rd party to connect the unit(s).
2. Do not try to open the unit for any reason.
3. Do not place any metal objects on the wireless charging surface.
4. Do not charge devices simultaneously when the total (including wireless and USB charger) charging power is over 5V 6A (30W).

MOUNTING

1. Bore a 3" hole using the specifications from the illustrations on the right.
2. Push the charger into the hole.
3. Connect the power adapter cord to the input jack on the bottom of the wireless charger.

USING WIRELESS CHARGER

1. Plug the power adapter to nearest wall outlet.
2. The LED indicator will flash briefly indicating the charger is correctly powered up.
3. Place the Qi wireless charging capable device on the DOCK-150. Blue indicator will be on for 10 seconds when it detects the device being charged. Once the device is fully charged the LED turns green indicating the charging is completed (green indicator works with compatible devices with status feedback functions only).

USING USB CHARGER

1. Press the center of the DOCK-150 to reveal the USB charging ports.
2. Select a charging port based on required max. charging current of the device being charged.
3. Plug in the USB type A connector to the port on the DOCK-150 to charge the device.
4. Remove all the USB type A connectors from the DOCK-150 and press the center again to hide the USB charging ports.

