

AIS MWall

Technical Information

Panels

- System accommodates beltline raceway with steel raceway “kick-plates”, with power and data both available at the beltline height.
- Beltline panels are interchangeable with non-beltline panels. Can interchange with bottom raceway, no raceway, or any combination of panels offered.
- Panels are 2” thick, with tackable core option.
- Panels have steel-to-steel connection system eliminating the use of separate 2-way, 3-way, 4-way, inline connections.
- Panels have steel lined top-channel raceway, and necessary accessory options to accommodate at least 50 pair Category 5 cables, and ability to bring cables to worksurface height.

Components

- Worksurfaces are 1 1/8” thick, use high-pressure laminate surface and backing, 2mm vinyl PVC edges.
- Pedestals have a minimum depth under a 24” deep worksurface of at least 23.75”, and all box and file drawers must have full extension ball bearing suspensions.
- Overhead locking storage units include steel and fabric covered, which open over top of cabinet, not a recessed door. Unit must be designed to not allow items to be placed on top of cabinet, and may not be a receding door.

Electrical:

- Uses 8 wire, 4 circuit electrical system.
- Ability to pass from a powered panel thru a non powered panel into a powered panel with a pass-through jumper extender.

General

- Must be new product, not refurbished or used.
- Product comes with Lifetime Warranty for manufacturer’s defects.
- 10 day quick-ship option, with a minimum of 125 standard fabrics, 30 standard laminates, and 9 paint options on quick ship program. Quick ship available for orders up to 200 workstations. Maximum lead time may not exceed 4 weeks, or 20 working days for any cataloged MWall product line.